

OCTOPUS™

“C” Series

Octopus Models: 1717



Standard configuration listed below.
Please contact your sales representative for additional options.

Structure

Aluminum frame

Performance

Speed: 20 rpm
Loads Per Hour: Up to 45 loads per hour depending on load size and wrap pattern
Maximum Load Size: 48W x 48”L x 94”H
Minimum Load Size: Depends (ask salesperson)
Maximum Load Weight: Dependent on conveyor

Shipping Information [Crated]

Dimensions: 118”L x 90”W x 47”H
Machine Weight: 2,860 Lbs.

Film Delivery System

Film Capacity: 20”W x 10”Dia.
Film Payout: Dancer bar
Pre-stretch Level: Up to 300%
Tension Control: Adjustable on HMI
Film Threading: Easy thread “S” carriage
Cut & Seal: Impulse heated cut wire and heat seal pad

Controls

PLC: Allen Bradley CompactLogix
Operator Interface: HMI
Load Height Sensing: Photoeye
Wrap Settings: Single Wrap, Double Wrap, Banding, Overlap, Overwrap
Electrical Safety: Category 3 Electrics
Disconnect Switch: Lockable
Electrical Enclosure: NEMA 12

Air & Power Requirements

Power: 480/3/60/30 Amps
Pneumatics: 80 PSI, 3 CFM

Ring Lift & Rotation

Lift Method: Reinforced Belt
Lift Motor: SEW Eurodrive
Rotation Method: Reinforced Belt
Rotation Motor: SEW Eurodrive

Additional Standard Features

Safety fence with electrical lockout switch
 Load indexing and safety photoeyes
 Automatic pass through

Optional Equipment

Pallet lift device
 Safety light curtains
 Roping device
 Ring Maintenance Locks
 Load stabilizer (gravity)
 Conveyors
 Tail Tucker
 And many more...

